




LED PERFORMANCE DAMPPROOF G4

كشاف ليد مقاوم للرطوبة



	Model number	L x W x H	W	V _{AC}	Hz	K	IP	IK	Beam angle	PF	👤
Dampproof 600 8W	P-DP06-8W-G4-830	599x77x68mm	8W	220-240V	50/60Hz	3000K	IP66	IK08	120°	≥0.9	730g
Dampproof 600 8W	P-DP06-8W-G4-840	599x77x68mm	8W	220-240V	50/60Hz	4000K	IP66	IK08	120°	≥0.9	730g
Dampproof 600 8W	P-DP06-8W-G4-865	599x77x68mm	8W	220-240V	50/60Hz	6500K	IP66	IK08	120°	≥0.9	730g
Dampproof 600 16W	P-DP06-16W-G4-830	599x77x68mm	16W	220-240V	50/60Hz	3000K	IP66	IK08	120°	≥0.9	730g
Dampproof 600 16W	P-DP06-16W-G4-840	599x77x68mm	16W	220-240V	50/60Hz	4000K	IP66	IK08	120°	≥0.9	730g
Dampproof 600 16W	P-DP06-16W-G4-865	599x77x68mm	16W	220-240V	50/60Hz	6500K	IP66	IK08	120°	≥0.9	730g
Dampproof 1200 14W	P-DP12-14W-G4-830	1199x77x68mm	14W	220-240V	50/60Hz	3000K	IP66	IK08	120°	≥0.9	1280g
Dampproof 1200 14W	P-DP12-14W-G4-840	1199x77x68mm	14W	220-240V	50/60Hz	4000K	IP66	IK08	120°	≥0.9	1280g
Dampproof 1200 14W	P-DP12-14W-G4-865	1199x77x68mm	14W	220-240V	50/60Hz	6500K	IP66	IK08	120°	≥0.9	1280g
Dampproof 1200 30W	P-DP12-30W-G4-830	1199x77x68mm	30W	220-240V	50/60Hz	3000K	IP66	IK08	120°	≥0.9	1280g
Dampproof 1200 30W	P-DP12-30W-G4-840	1199x77x68mm	30W	220-240V	50/60Hz	4000K	IP66	IK08	120°	≥0.9	1280g
Dampproof 1200 30W	P-DP12-30W-G4-865	1199x77x68mm	30W	220-240V	50/60Hz	6500K	IP66	IK08	120°	≥0.9	1280g
Dampproof 1500 21W	P-DP15-21W-G4-830	1499x77x68mm	21W	220-240V	50/60Hz	3000K	IP66	IK08	120°	≥0.9	1540g
Dampproof 1500 21W	P-DP15-21W-G4-840	1499x77x68mm	21W	220-240V	50/60Hz	4000K	IP66	IK08	120°	≥0.9	1540g
Dampproof 1500 21W	P-DP15-21W-G4-865	1499x77x68mm	21W	220-240V	50/60Hz	6500K	IP66	IK08	120°	≥0.9	1540g
Dampproof 1500 43W	P-DP15-43W-G4-830	1499x77x68mm	43W	220-240V	50/60Hz	3000K	IP66	IK08	120°	≥0.9	1540g
Dampproof 1500 43W	P-DP15-43W-G4-840	1499x77x68mm	43W	220-240V	50/60Hz	4000K	IP66	IK08	120°	≥0.9	1540g
Dampproof 1500 43W	P-DP15-43W-G4-865	1499x77x68mm	43W	220-240V	50/60Hz	6500K	IP66	IK08	120°	≥0.9	1540g
Dampproof 1500 57W	P-DP15-57W-G4-830	1499x77x68mm	57W	220-240V	50/60Hz	3000K	IP66	IK08	120°	≥0.9	1550g
Dampproof 1500 57W	P-DP15-57W-G4-840	1499x77x68mm	57W	220-240V	50/60Hz	4000K	IP66	IK08	120°	≥0.9	1550g
Dampproof 1500 57W	P-DP15-57W-G4-865	1499x77x68mm	57W	220-240V	50/60Hz	6500K	IP66	IK08	120°	≥0.9	1550g

150
lm/W

50000h

SMD
LED









LEDVANCE





LED PERFORMANCE DAMPPROOF G4 | كشاف ليد مقاوم للرطوبة









2











LED PERFORMANCE DAMPPROOF G4 | كشاف ليد مقاوم للرطوبة













LED PERFORMANCE DAMPPROOF G4 | كشاف ليد مقاوم للرطوبة





LED PERFORMANCE DAMPPROOF G4 | كشاف ليد مقاوم للرطوبة





WARNING:

- The light source contained in this luminaire shall only be replaced by the manufacturer or his service agent or a similar qualified person.
- Connect to the power supply in accordance with national regulations. And make sure the power supply is off when connecting.
- This product is to be installed by a licensed electrician in strict accordance with local wiring rules.
- Please note that the fixture is equipped with standard surge protection only. To protect the fixture from sags, surges, and lighting strikes, additional surge protectors must be deployed on the primary side.

تحذير

- يجب استبدال مصدر الضوء الموجود في وحدة الإنارة فقط عن طريق المصنِّع أو وكيل الخدمة أو شخص مؤهل مماثل.
- قم بتوصيل التيار الكهربائي وفقاً للوائح الوطنية وتأكد من فصل التيار الكهربائي عند التوصيل.
- هذا المنتج يجب أن يتم تثبيته من قبل كهربائي مرخص وفقاً لقواعد التوصيل المحلية.
- ملاحظة: وحدة الإضاءة هذه مزودة بحماية من نبضات الفولتية اللحظية المرتفعة حسب المواصفات المعتمدة عالمياً

LEDVANCE Pte, Ltd.
320 Serangoon Road #14-02,
Centrium Square 218108, Singapore.
Phone +65 6911 8260

LEDVANCE Sdn, Bhd, (1166537-U)
100.7.009, 129 Offices, Block J, Jaya One
No. 72A, Jalan Universiti,
46200 Petaling Jaya,
Selangor Darul Ehsan, Malaysia

(주)레드밴스
서울시 강남구 삼성로 554 예성빌딩6층
(우편번호 06165)
전화번호: +82 80 489 1700
www.ledvance.co.kr

LEDVANCE MIDDLE EAST FZE
Office No. LB040123
PO Box 17476, Jebel Ali Free Zone
Dubai, United Arab Emirates
Tel.: +971 4 881 37 67
Fax: +971 4 881 37 69

LEDVANCE Prosperity Co., Ltd.
20/F, Cornell Centre, 50 Wing Tai Rd.,
Chai Wan, Hong Kong

LEDVANCE Pvt. Ltd.
1201-1202, 12th Floor, Signature Towers, Tower-A,
South City-I, Gurugram-122001, Haryana (India)
Consumer care cell (Name and address as per above),
Consumer care Tel. No. 0124-4150100
Toll Free Number – 18001026258
E-mail id: customercare@ledvance.com
www.ledvance.in



C10449057
G11174980
2023-08-09

www.ledvance.com

