

# PRODUCT DATASHEET

## HQL LED 4000 lm 30 W/4000K E27

HQL LED PRO | LED replacement for HID lamps for outdoor application



### AREAS OF APPLICATION

- Streets
- Area lighting
- Pedestrian zones
- Parks
- Industry
- Outdoor applications only in suitable luminaires

### PRODUCT BENEFITS

- Saves up to 78 % energy when used as replacement for mercury vapor lamps (HQL)
- Effective thermal management for wide operating temperature range
- Low maintenance costs thanks to long lifetime
- Instant 100 % light, no warm-up time

### PRODUCT FEATURES

- LED alternative for applications requiring a high luminous flux
- Power factor: 0.9
- Type of protection: IP65
- High surge protection: up to 4 kV (L-N)
- Replacement for HQL: Suitable for operation with conventional control gear for HQL
- Replacement for other HID: Suitable for operation with line voltage without control gear



## TECHNICAL DATA

### Electrical data

Rated wattage	30.00 W
Nominal wattage	30.00 W
Nominal voltage	220...240 V
Max. lamp no. on circuit break. 10 A (B)	42
Max. lamp no. on circuit break. 16 A (B)	68
Operating frequency	50/60 Hz
Inrush current	4.6 A
Power factor $\lambda$	0.90


### Photometrical data

Nominal luminous flux	4000 lm
Rated luminous flux	4000 lm
Rated color temperature	4000 K
Lumen main.fact.at end of nom.life time	0.70
Light color (designation)	Cool White
Color temperature	4000 K
Luminous flux	4000 lm
Color rendering index Ra	$\geq 80$
Standard deviation of color matching	$\leq 6$ sdcn
Color rendering index Ra	$\geq 80$

### Light technical data

Warm-up time (60 %)	< 0.50 s
Beam angle	360 °
Starting time	< 0.5 s

### Dimensions & weight



<b>Overall length</b>	170.0 mm
<b>Diameter</b>	75.0 mm
<b>Outer bulb</b>	-
<b>Length</b>	170.0 mm

#### Temperatures & operating conditions

<b>Ambient temperature range</b>	-20...+60 °C
<b>Maximum temperature at tc test point</b>	86 °C

#### Lifespan

<b>Nominal lamp life time</b>	50000 h
<b>Rated lamp life time</b>	50000 h
<b>Number of switching cycles</b>	100000
<b>Lumen maintenance at end of service life</b>	0.70

#### Additional product data

<b>Base (standard designation)</b>	E27
<b>Mercury content</b>	0.0 mg
<b>Mercury-free</b>	Yes
<b>Design / version</b>	Clear
<b>Show WEEE picto</b>	Yes

#### Capabilities

<b>Dimmable</b>	No
-----------------	----


#### Certificates & standards

<b>Energy efficiency class</b>	A++
<b>Energy consumption</b>	30 kWh/1000h


#### Country-specific categorizations

<b>Order reference</b>	HQLLED4000 30W/
------------------------	-----------------

Light Distribution



LDC typ polar



Spectral power distribution

SAFETY ADVICE

- The bulb may be larger and heavier than the replaced bulb. Before installation it must be checked, if the luminaire and especially the holder is capable of carrying the weight of the lamp.  
Not suitable for operation with ignitors  
Operation on the capacitor can lead to a reduction of the power factor of the system.

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075124820	Folding carton box 1	82 mm x 82 mm x 201 mm	543.00 g	1.35 dm <sup>3</sup>
4058075124837	Shipping carton box 6	255 mm x 175 mm x 226 mm	3514.00 g	10.09 dm <sup>3</sup>

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.