

## PRODUCT DATASHEET

### ST5HE-AC 15 W/6500 K 1149.00 mm

SubstiTUBE T5 220-240V AC | LED tubes for operation on AC mains connection



#### Areas of application

- Offices, public buildings
- Supermarkets and department stores
- Industry
- General illumination within ambient temperatures from -20...+45 °C

#### Product benefits

- No bending thanks to glass technology
- Shatter protection thanks to special PET coating
- High luminous flux for sophisticated lighting tasks

#### Product features

- LED replacement for T5 fluorescent lamps with G5 base on AC mains
- Lamp tube made of glass with splinter protection e.g. for food industry applications
- High color consistency:  $\leq 5$  sdcm
- Lifetime up to 50,000 h
- Low flicker according to EU 2019/2020
- Type of protection: IP20



## TECHNICAL DATA

### Electrical data

Nominal wattage	15 W
Construction wattage	15.00 W
Nominal voltage	220...240 V
Nominal current	70 mA
Type of current	AC
Operating frequency	50...60 Hz
Mains frequency	50...60 Hz
Total harmonic distortion	≤ 20 %
Power factor $\lambda$	> 0.90

### Photometrical data

Luminous flux	1800 lm
Luminous efficacy	120 lm/W
Light color (designation)	Cool Daylight
Color temperature	6500 K
Color rendering index Ra	> 80
Light color	865
Standard deviation of color matching	≤5 sdcn

### Light technical data

Beam angle	180 °
------------	-------

### Dimensions & Weight

Overall length	1149.00 mm
Diameter	16.00 mm
Product weight	160.00 g

### Temperatures & operating conditions

Ambient temperature range	-20...+45 °C
---------------------------	--------------

### Lifespan

Number of switching cycles	30000
----------------------------	-------

### Additional product data

Base (standard designation)	G5
-----------------------------	----

Mercury content	0.0 mg
Mercury-free	Yes

### Capabilities

Dimmable	No
----------	----

### Certificates & Standards

Type of protection	IP20
Standards	CE

### Country-specific categorizations

Order reference	ST5HEV-1.2M 15W
-----------------	-----------------

### LOGISTICAL DATA

Temperature range at storage	-20...+80 °C
------------------------------	--------------

### Energy labelling regulation data acc EU 2019/2015

Light source cap-type (or other electric interface)	G5
Length	1149.00 mm
Height	16.00 mm
Width	16.00 mm

### Safety advice

- Not suitable for operation with electronic control gear.
- Operation in outdoor applications in suitable damp-proof luminaires possible according to data sheet and installation instruction.
- The operating temperature range of LED tube is restricted. In case of doubt regarding suitability of the application please measure Tc temperature on the product prior to installation.

### LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075556454	Sleeve 1	1,165 mm x 20 mm x 24 mm	178.00 g	0.56 dm <sup>3</sup>
4058075556461	Shipping box 10	1,218 mm x 153 mm x 80 mm	2198.00 g	14.91 dm <sup>3</sup>

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

### DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.