

# PRODUCT DATASHEET SMART+ Wifi Planon 1200x100mm RGB + TW

SMART+ Planon Frameless TW and Multicolor | Frameless panel luminaires with WiFi technology

#### Areas of application

- Indoor applications
- Kitchens, living rooms, children's rooms or home offices



## Product benefits

- Easy and quick installation

#### **Product features**

- Controllable via LEDVANCE SMART+ App (with minimum Android 8.0 or iOS 14.0)
- Controllable via voice control available: Google Assistant or Amazon Alexa
- RGB color control, approx. 16 million color options adjustable
- Adjustable color temperature via Tunable White: 3,000...6,500 K
- Dimmable
- Network protocol: WiFi



## **TECHNICAL DATA**

## Electrical data

Nominal wattage35.00 WNominal voltage220240 VMains frequency5060 HzNominal current176.000 mAMax. number of luminaires per miniature circuit breaker B1616Max. number of luminaires per miniature circuit breaker C1624Power factor λ> 0.90Total harmonic distortion< 20 %Protection classIIOperating modeMains voltage		
Mains frequency5060 HzNominal current176.000 mAMax. number of luminaires per miniature circuit breaker B1616Max. number of luminaires per miniature circuit breaker C1624Power factor λ> 0.90Total harmonic distortion< 20 %	Nominal wattage	35.00 W
Nominal current176.000 mAMax. number of luminaires per miniature circuit breaker B1616Max. number of luminaires per miniature circuit breaker C1624Power factor λ> 0.90Total harmonic distortion< 20 %	Nominal voltage	220240 V
Max. number of luminaires per miniature circuit breaker B16       16         Max. number of luminaires per miniature circuit breaker C16       24         Power factor λ       > 0.90         Total harmonic distortion       < 20 %	Mains frequency	5060 Hz
Max. number of luminaires per miniature circuit breaker C16       24         Power factor λ       > 0.90         Total harmonic distortion       < 20 %	Nominal current	176.000 mA
Power factor λ > 0.90  Total harmonic distortion < 20 %  Protection class II	Max. number of luminaires per miniature circuit breaker B16	16
Total harmonic distortion < 20 %  Protection class II	Max. number of luminaires per miniature circuit breaker C16	24
Protection class II	Power factor $\lambda$	> 0.90
	Total harmonic distortion	< 20 %
Operating mode Mains voltage	Protection class	II
	Operating mode	Mains voltage

## Photometrical data

Luminous flux	2500 lm	
Total luminous flux of contained light sources	4100 lm	
Luminous efficacy	71 lm/W	
Color temperature	30006500 K	
Light color (designation)	Tunable White / RGB	
Color rendering index Ra	> 80	
Standard deviation of color matching	< 6 sdcm	
Flickering metric (Pst LM)	≤1	
Stroboscope effect metric (SVM)	≤0.4	
Photobiological safety group acc. to EN62778	RG0	
Photobiological safety group acc. to EN62471	RG0	
Beam angle	110°	

## Dimensions & Weight

Length	1200.00 mm
Width	100.00 mm
Height	64.00 mm
Product weight	2630.00 g

SMART WIFI PLANON FRAMELESS120X10

## Materials & Colors

Product color	White	
Housing color	White	
Body material	Aluminum	
Cover material	Polymethylmethacrylate (PMMA)	
Light emitting surface material	PMMA	
Glow Wire Test according to IEC 60695-2-12	650 °C	
Mercury content	0.0 mg	

## **Application & Mounting**

Ambient temperature range	-20+40 °C	
Type of connection	Terminal, 2-Pole (L, N)	
Type of protection	IP20	
Dimmable	Yes	
Type of dimming	WiFi	
Mounting type	Surface	
Mounting location	Ceiling	
Application environment	Indoor	
With light source	No	

## Lifespan

Lifespan L70/B50 at 25 °C	25000 h
Number of switching cycles	15000

## Certificates & Standards

Standards	CE / EAC / UKCA
Luminaire with limited surface temperature, "D sign"	No
Replaceable light source (EPREL)	Not replaceable

# Additional product data

and off for three seconds and repeating this five times.	Product remark	Reset settings to default by switching the product on for three seconds and off for three seconds and repeating this five times.
--	----------------	--

## **EQUIPMENT / ACCESSORIES**

- Mounting bracket included

- Mounting screws and dowels included
- Control via app or voice control requires compatible Smart home system
- For control via LEDVANCE SMART+ App, a smartphone or tablet is required (with minimum Android 8.0 or iOS 14.0)

#### Safety advice

- All electrical connections must be made by a qualified person.
- Caution, risk of electric shock.
- Check wall-ceiling for suitability. If uncertain, seek professional advice.

#### **DOWNLOAD DATA**

	Documents and certificates	Document name	
PDF	User instruction / safety instructions	SMART+ PLANON FRAMELESS	
PDF	User instruction / safety instructions	SMART+ PLANON FRAMELESS	
PDF	Declarations of conformity	SMART WIFIPLANONFRAMELESS120X10RGBW	
PDF	Declarations of conformity UKCA	SMART WIFI AND SUNATHOME	
PDF	EU Data Act	SMART WiFi Lamps and Luminaires	

#### LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075484573	Folding box 1	95 mm x 1,237 mm x 135 mm	2928.00 g	15.86 dm <sup>3</sup>
4058075484580	Shipping box	1,254 mm x 304 mm x 305 mm	19064.00 g	116.27 dm <sup>3</sup>

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

#### References / Links

- Further information and frequently asked questions (FAQs) at www.ledvance.com/consumer/smart/faq

#### **DISCLAIMER**

TW

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.