

PRODUCT DATASHEET LVED VAL 200/220-240/700 P

LED VAL Outdoor CC Driver | Constant current driver for LED modules



TECHNICAL DATA

Electrical data

Nominal wattage	200.00 W
Nominal voltage	220240 V
Nominal output voltage	200285 V
Nominal output current	700 mA
Output current tolerance	+/- 5 %
Output ripple current (100 Hz)	≤ 5 %
Mains frequency	5060 Hz
Total harmonic distortion	< 10 % ¹⁾
Power factor λ	> 0.95 ¹⁾
ECG efficiency	≥94.5 % ¹⁾
Surge capability (L/N-Ground)	6 kV
Surge capability (L-N)	6 kV

¹⁾ At full load

Dimensions & Weight



Length	150.00 mm
Width	66.40 mm
Height	36.70 mm
Cable cross-section, input side	3*1.0 mm ²
Cable cross-section, output side	2*1.0 mm ²
Product weight	630.00 g

Temperatures & operating conditions

Ambient temperature range	-40+55 °C
Maximum temperature at tc test point	90 °C

Lifespan

Ī	ECC lifetime	50000 h
	ECG lifetime	3000011

Capabilities

Dimmable	No
----------	----

Overheating protection	Yes
Overload protection	Yes
Short-circuit protection	Yes

Certificates & Standards

Approval marks – approval	CB / KC
Protection class	1
Type of protection	IP67

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4099854039607	Unpacked 1		630.00 g	
4099854039614	Shipping box 18	436 mm x 336 mm x 151 mm	11980.00 g	22.12 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.