

PRODUCT DATASHEET

LN INV DI 1200 P 54W 930 DAVR BK

LINEAR INDIVILED DIRECT/INDIRECT 1200 DALI | Pendant luminaire for single or light line office application with CRI90 and DALI-2 IoT technology, 1200 mm



Areas of application

- Direct replacement for luminaires with fluorescent lamps
- Offices, education, public buildings
- Single and continuous line configuration
- Direct and indirect lighting

Product benefits

- Easy upgradeability of light source and driver (EVERLOOP design)
- Homogenous light distribution and reduced glare ($UGR \leq 19$) thanks to IndiviLED® optics
- Pendant luminaires with direct light emission (70%) and indirect light emission (30%)
- High performance with CRI90 and up to 137 lm/W
- IoT-ready luminaire with DALI-2 driver, suitable for VIVARES and other Light Management Systems
- Extended services such as energy monitoring and remote maintenance possible with DALI versions
- High color consistency with SDCM 3
- Easy installation
- Low flicker light thanks to special electronic control gear
- Suitable for battery emergency installations acc. to EN 60598-2-22
- Multiple mounting options thanks to different accessories

Product features

- Minimalistic LEDVANCE SCALE design in extruded aluminum housing, available in white and black color



- Includes EVERLOOP: Convenient replacement of light source and LED driver
- Linkable into seamless light line with accessories (surface or pendant mounting)
- Pendant mounting with suspension kit (to be ordered separately)
- Glow Wire Test according to IEC 60695-2-12: 850 °C
- 5-pole terminal block, cable cross section up to 5 x 2.5 mm²
- Lifetime (L80/B10): 70,000 h (at 25 °C)


TECHNICAL DATA

Electrical data


Nominal wattage	54 W / 48 W / 43 W / 34 W
Nominal voltage	220...240 V
Mains frequency	0/50/60 Hz
Nominal current	233...205...195...160 mA
Inrush current	25.2 A
Inrush current time T_{h50}	40 μ s
Max. number of luminaires per miniature circuit breaker B16	29
Max. number of luminaires per miniature circuit breaker C10	23
Max. number of luminaires per miniature circuit breaker C16	38
Power factor λ	> 0.90
Total harmonic distortion	$\leq$ 20 %
Protection class	I
Operating mode	Integrated LED driver
Dimming interface	DALI-2 / IoT

Photometrical data

Luminous flux	4250 lm / 5100 lm / 5650 lm / 6400 lm
Luminous efficacy	125 lm/W / 119 lm/W / 118 lm/W
Color temperature	3000 K
Light color (designation)	Warm White
Color rendering index Ra	> 90
Standard deviation of color matching	3 sdc _m
Low flicker	Yes
Flickering metric (Pst LM)	$\leq$ 1
Stroboscope effect metric (SVM)	$\leq$ 0.4
Photobiological safety group acc. to EN62778	RG0
Photobiological safety group acc. to EN62471	RG0
Beam angle	90 ° + 130 °
UGR	< 19



LN INV DI 1200 P 54W 930 DAVR BK 1100mA




LN INV DI 1200 P 54W 930 DAVR BK 1100mA

Adjustable attributes

Nominal wattage	Color temperature	Luminous flux	Luminous efficacy
54 W	3000 K	6400 lm	119 lm/W
48 W	3000 K	5650 lm	118 lm/W
43 W	3000 K	5100 lm	119 lm/W
34 W	3000 K	4250 lm	125 lm/W

Dimensions & Weight

Length	1210.00 mm
Width	125.00 mm
Height	43.00 mm
Product weight	3590.00 g



LN INV 1200 P

Materials & Colors

Product color	Black
Housing color	Black
Body material	Aluminum
Cover material	Polymethylmethacrylate (PMMA)
Light emitting surface material	Polymethylmethacrylate (PMMA)
Glow Wire Test according to IEC 60695-2-12	850 °C
Mercury content	0.0 mg

Application & Mounting

Ambient temperature range	-20...+50 °C
Temperature range at storage	-20...+80 °C
Type of connection	Screwless terminal, 5-Pole (L, N, PE, DA+, DA-)
Type of protection	IP20
Protection class IK (shock resistance)	IK06
Dimmable	Yes
Type of dimming	DALI2
Mounting type	Suspended
Mounting location	Ceiling
Application environment	Indoor
Adjustable	No
With light source	Yes
Replaceable light source	Yes

Lifespan

Lifespan L70/B50 at 25 °C	100000 h ¹⁾
Lifespan L80/B10 at 25 °C	70000 h ¹⁾
Lifespan L80/B50 at 25 °C	70000 h
Lifespan L90/B10 at 25 °C	35000 h
Number of switching cycles	25000

1) t[h]: L70 / B50 @ 25 °C (Ta), t[h]: L80 / B10 @ 25 °C (Ta), t[h]: L90 / B10 @ 25 °C (Ta)

Control gear

Output current	1100mA / 950mA / 850mA / 700 mA
ECG - Output ripple current	≤ 5 %
Recommended control gear	OSRAM type OTI DALI 50/220-240/1A4 NFC L

Certificates & Standards

Standards	CE / CB / ENEC / TÜV SÜD / UKCA / EAC / EPD
Luminaire with limited surface temperature, "D sign"	No
Ball shot safe	No
EPD	LEDV-00026-V01.01-EN
Replaceable light source (EPREL)	By the end consumer

Additional product data

Number of illuminants	2
Added function	EVERLOOP / VIVARES

Accessories Mandatory

Product image	Product name	EAN
	LN INV SUSPENSION KIT BK	4099854297069

Accessories Optional

Product image	Product name	EAN
		4099854297083

Product image	Product name	EAN
	LN INV INFILL 600 BK	4099854297045
	LN INV INFILL 1200 BK	4099854297007
	LN INV INFILL 1500 BK	4099854297021
	LN INV SUSPENSION WIRE	4099854215551
	LN INV 1200 THROUGHWIRING KIT	4099854214820
	LN INV INLINE CONNECTOR	4099854215612

EQUIPMENT / ACCESSORIES

- Suspension kit available for pendant luminaire version (to be ordered separately)
- Inline, corner and infill connectors available as separate accessory
- Through-wiring cable kit available

Safety advice

- All electrical connections must be made by a qualified person.
- If the external flexible cable or cord of this luminaire is damaged, it shall be exclusively replaced by a qualified person in order to avoid a hazard.
- Caution, risk of electric shock.
- Product in protection class I. All electrically conductive, metallic housing parts that can absorb voltage during operation or during maintenance in the event of a fault must be continuously connected to the protective earthing conductor.

DOWNLOAD DATA


Documents and certificates		Document name
	User instruction / safety instructions	LN INV D PS
	Legal information	Legal Insert LN INV P DA
	Legal information	LSI LN INV DAVR WT
	Declarations of conformity	LN INV
	Declarations of conformity UKCA	LN INV
	Certificates	LN INV
Photometric and lighting design files		Document name
	IES file (IES)	LN INV DI 1200 P 54W 930 DAVR BK 1100mA
	LDT file (Eulumdat)	LN INV DI 1200 P 54W 930 DAVR BK 1100mA
	ULD file (DIALux)	LN INV DI 1200 P 54W 930 DAVR BK
	ROLF file (RELUX)	LN INV DI 1200 P 54W 930 DAVR BK
	UGR file (UGR table)	LN INV DI 1200 P 54W 930 DAVR BK 1100mA
	Light distribution curve type cone	LN INV DI 1200 P 54W 930 DAVR BK 1100mA
	Light distribution curve type polar	LN INV DI 1200 P 54W 930 DAVR BK 1100mA
CAD/BIM files		Document name
	BIM Revit 3D	Linear Indiviled G2
	CAD STEP 3D	LN INV D I 1200 G2

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4099854296840	Folding box 1	178 mm x 1,263 mm x 103 mm	4140.00 g	23.16 dm³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

LINEAR INDEGREE/ OUTDEGREE DAILY	DRIVER	DIRECT		INDIRECT		Total		DATA
		MA	SA	MA	SA	MA	SA	Weight
LN IN/EN DE 1200 / 5400 S400 D400 SIK	OSIRIS	400	200	200	200	600	600	0.00%
	OSIRIS	200	200	200	200	400	400	0.00%
	200-240/	200	200	200	200	400	400	0.00%
	240-240/	200	200	200	200	400	400	0.00%
LN IN/EN DE 1200 / 5400 S400 D400 SIK	OSIRIS	400	200	200	200	600	600	0.00%
	OSIRIS	200	200	200	200	400	400	0.00%
	200-240/	200	200	200	200	400	400	0.00%
	240-240/	200	200	200	200	400	400	0.00%
LN IN/EN DE 1200 / 5400 S400 D400 SIK	OSIRIS	400	200	200	200	600	600	0.00%
	OSIRIS	200	200	200	200	400	400	0.00%
	200-240/	200	200	200	200	400	400	0.00%
	240-240/	200	200	200	200	400	400	0.00%
LN IN/EN DE 1200 / 5400 S400 D400 SIK	OSIRIS	400	200	200	200	600	600	0.00%
	OSIRIS	200	200	200	200	400	400	0.00%
	200-240/	200	200	200	200	400	400	0.00%
	240-240/	200	200	200	200	400	400	0.00%
LN IN/EN DE 1200 / 5400 S400 D400 SIK	OSIRIS	400	200	200	200	600	600	0.00%
	OSIRIS	200	200	200	200	400	400	0.00%
	200-240/	200	200	200	200	400	400	0.00%
	240-240/	200	200	200	200	400	400	0.00%
LN IN/EN DE 1200 / 5400 S400 D400 SIK	OSIRIS	400	200	200	200	600	600	0.00%
	OSIRIS	200	200	200	200	400	400	0.00%
	200-240/	200	200	200	200	400	400	0.00%
	240-240/	200	200	200	200	400	400	0.00%



– For Guarantee see www.ledvance.com/guarantee

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.