

PRODUCT DATASHEET LED PAR1635 RECH 3,5W/6500K GU10

LED RECHARGEABLE PAR16 | Battery Backup lighting



Areas of application

- Residential interiors
- Restaurants
- Commercial applications
- Museums, art galleries

Product benefits

- Reliable operation thanks to brand quality
- Can work as emergency lamp when black out
- Can use as normal LED bulb when have power

Product features

- Long lifetime up to 15,000 h
- Over Temperature Protection
- Rechargeable more than 300 times, 100% depth of discharge



TECHNICAL DATA

Electrical data

Nominal wattage	3.5 W
Construction wattage	3.50 W
Nominal voltage	220240 V
Claimed equiv. conventional lamp power	35 W
Nominal current	30 mA
Operating frequency	50/60 Hz
Mains frequency	50/60 Hz
Power factor λ	> 0.50

Photometrical data

Luminous flux	350 lm
Luminous efficacy	100 lm/W
Color temperature	6500 K
Color rendering index Ra	> 80
Light color	865
Standard deviation of color matching	≤6 sdcm

Light technical data

Starting time ≤ 0.5 s	
-----------------------	--

Dimensions & Weight

Overall length	53.00 mm		
Diameter	50.00 mm		
Product weight	36.00 g		
Temperatures & operating conditions			
Ambient temperature range	-10+45 °C		
Lifespan			

2100000

Number of switching cycles

Additional product data

Base (standard designation)	GU10
Design / version	Frosted

BATTERY

Battery size [GMS]	Others
Battery charging time	10 h

Capabilities

Ī	Dimmable	No

Certificates & Standards

Type of protection	IP20

Country-specific categorizations

Order reference	LPRECHPR1635 3,
-----------------	-----------------

LOGISTICAL DATA

Temperature range at storage	-10+70 °C ¹⁾

¹⁾ can stage 6-8 hours under 70°C

Energy labelling regulation data acc EU 2019/2015

Light source cap-type (or other electric interface)	GU10
Length	53.00 mm
Height	50.00 mm
Width	50.00 mm

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4099854184987	Folding box 1	52 mm x 52 mm x 60 mm	53.00 g	0.16 dm ³
4099854184994	Shipping box 10	276 mm x 115 mm x 77 mm	590.00 g	2.44 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.