

PRODUCT DATASHEET SMART+ Wifi Flare Wall RGB + W

Smart+ Flare Multicolor | Luminaires with WiFi technology



Areas of application

- General illumination
- Gardens
- Patios, balconies

Product benefits

- Easy and quick installation
- Colorful garden lighting with smart and intelligent control options

Product features

- Controllable via LEDVANCE SMART+ App (with minimum Android 8.0 or iOS 14.0)
- Controllable via voice control available: Google Assistant or Amazon Alexa
- RGB color control, approx. 16 million color options adjustable
- Dimmable
- Color temperature: 3,000 K (Warm White)
- Network protocol: WiFi
- Type of protection: IP44



TECHNICAL DATA

Electrical data


| Nominal wattage | 7.50 W | |
|---------------------------|---------------|--|
| Nominal voltage | 220240 V | |
| Mains frequency | 5060 Hz | |
| Power factor λ | > 0.5 | |
| Total harmonic distortion | ≤ 20 % | |
| Protection class | I | |
| Operating mode | Mains voltage | |

Photometrical data

| Luminous flux | 320 lm | |
|--|----------|--|
| Total luminous flux of contained light sources | 570 lm | |
| Luminous efficacy | 43 lm/W | |
| Color temperature | 3000 K | |
| Light color (designation) | RGBW | |
| Color rendering index Ra | ≥80 | |
| Standard deviation of color matching | < 6 sdcm | |
| Photobiological safety group acc. to EN62778 | RG0 | |
| Photobiological safety group acc. to EN62471 | RG0 | |
| Beam angle | 230.00 ° | |

Dimensions & Weight

| Length | 98.00 mm |
|----------------|-----------|
| Width | 66.00 mm |
| Height | 331.00 mm |
| Product weight | 900.00 g |



Materials & Colors

| Product color | Dark gray | |
|--|--------------------|--|
| Housing color | Dark gray | |
| Body material | Aluminum | |
| Cover material | Polycarbonate (PC) | |
| Glow Wire Test according to IEC 60695-2-12 | 650 °C | |

Application & Mounting

| Ambient temperature range | -20+40 °C |
|--|-----------------------------|
| Type of connection | Terminal, 3-Pole (L, N, PE) |
| Type of protection | IP44 |
| Protection class IK (shock resistance) | IK03 |
| Dimmable | Yes |
| Type of dimming | WiFi |
| Mounting type | Surface |
| Mounting location | Wall |
| Application environment | Outdoor |
| With light source | No |

Lifespan

| Lifespan L70/B50 at 25 °C | 25000 h |
|----------------------------|---------|
| Number of switching cycles | 12500 |

Certificates & Standards

| Standards | CE / EAC / UKCA |
|-----------|-----------------|
|-----------|-----------------|

| Luminaire with limited surface temperature, "D sign" | No |
|--|-----------------|
| Replaceable light source (EPREL) | Not replaceable |

Additional product data

| Product remark Reset settings to default by switching the product on for three seconds and off for three seconds and repeating this five times. |
|--|
|--|

EQUIPMENT / ACCESSORIES

- Mounting screws and dowels included
- Control via app or voice control requires compatible Smart home system
- For control via LEDVANCE SMART+ App, a smartphone or tablet is required (with minimum Android 8.0 or iOS 14.0)

Safety advice

- All electrical connections must be made by a qualified person.
- Caution, risk of electric shock.
- Product in protection class I. All electrically conductive, metallic housing parts that can absorb voltage during operation or during maintenance in the event of a fault must be continuously connected to the protective earthing conductor.

DOWNLOAD DATA

| | Documents and certificates | Document name | |
|-----|--|---------------------------------------|--|
| POF | User instruction / safety instructions | SMART OUTD WIFI FLARE | |
| POF | Legal information | Legal insert | |
| POF | Declarations of conformity | CE_SMART OUTD WIFI FLARE WALL RGBW DG | |
| POF | Declarations of conformity UKCA | SMART WIFI | |

LOGISTICAL DATA

| Product code | Packaging unit (Pieces/Unit) | Dimensions (length x width x height) | Gross weight | Volume |
|---------------|------------------------------|--------------------------------------|--------------|-----------------------|
| 4058075478275 | Folding box 1 | 117 mm x 87 mm x 354 mm | 979.00 g | 3.60 dm ³ |
| 4058075478282 | Shipping box 4 | 368 mm x 248 mm x 199 mm | 4321.00 g | 18.16 dm ³ |

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

References / Links

- Further information and frequently asked questions (FAQs) at www.ledvance.com/consumer/smart/faq

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.