

PRODUCT DATASHEET

LED VALUE STICK 7.2 W/4000 K G24d

LED VALUE STICK TruWave | LED lamps, classic stick shape with TruWave Technology™



Areas of application

- All domestic rooms, especially where the lamps are visible
- Wherever compact and efficient lamps are needed
- Where the lamps need to last a long time or have to withstand frequent on/off switching

Product benefits

- LED lamps with innovative TruWave Technology™
- Support sleep/wake cycle thanks mimic of the natural light spectrum
- The balanced blue light spectrum can support attention, reaction time and mood
- Low energy consumption
- Attractive lamp appearance

Product features

- LED alternative to conventional lamps
- Input voltage: 220...240 V_{AC}
- Color rendering index $R_a \geq 80$
- Lifetime up to 15,000 h
- Mercury-free lamps



TECHNICAL DATA

Electrical data

| | |
|-------------------------------|-------------|
| Nominal wattage | 7.2 W |
| Construction wattage | 7.20 W |
| Nominal voltage | 220...240 V |
| Nominal current | 72 mA |
| Type of current | AC |
| Operating frequency | 50/60 Hz |
| Mains frequency | 50/60 Hz |
| Max. lamp number on MCB B10 A | 182 |
| Max. lamp number on MCB B16 A | 291 |

Photometrical data

| | |
|---------------------------|------------|
| Luminous flux | 806 lm |
| Luminous efficacy | 111 lm/W |
| Light color (designation) | Cool White |
| Color temperature | 4000 K |
| Color rendering index Ra | 80 |
| Light color | 840 |

Dimensions & Weight

| | |
|----------------|-----------|
| Overall length | 120.00 mm |
| Diameter | 40.50 mm |
| Product weight | 34.00 g |

Temperatures & operating conditions

| | |
|---------------------------|--------------|
| Ambient temperature range | -20...+40 °C |
|---------------------------|--------------|

Additional product data

| | |
|-----------------------------|------|
| Base (standard designation) | G24d |
|-----------------------------|------|

Certificates & Standards

| | |
|--|------|
| Type of protection | IP20 |
| Standards | LVD |
| Photobiological safety group acc. to EN62778 | RG0 |

Country-specific categorizations

| | |
|-----------------|-----------------|
| Order reference | LVSTICK 7,2W/84 |
|-----------------|-----------------|

LOGISTICAL DATA

| | |
|------------------------------|--------------|
| Temperature range at storage | -20...+80 °C |
|------------------------------|--------------|

Energy labelling regulation data acc EU 2019/2015

| | |
|---|-----------|
| Light source cap-type (or other electric interface) | G24d |
| Length | 120.00 mm |
| Height | 40.50 mm |
| Width | 40.50 mm |

LOGISTICAL DATA

| Product code | Packaging unit (Pieces/Unit) | Dimensions (length x width x height) | Gross weight | Volume |
|---------------|------------------------------|--------------------------------------|--------------|----------------------|
| 4099854036613 | Folding box 1 | 43 mm x 43 mm x 119 mm | 49.00 g | 0.22 dm ³ |
| 4099854036620 | Shipping box 10 | 222 mm x 93 mm x 119 mm | 562.00 g | 2.46 dm ³ |
| 4099854316227 | Shipping box 10 | 227 mm x 102 mm x 149 mm | 800.00 g | 3.45 dm ³ |

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.