

# PRODUCT DATASHEET LED VALUE CLAS A 12 W/6500 K E27 GEN2

LED VALUE CLASSIC A | LED lamps, classic bulb shape



#### Areas of application

- Domestic applications
- General illumination
- Outdoor applications only in suitable luminaires

#### **Product benefits**

- No "Blue Light" Hazard (according to IEC62778)
- Photobiological safety according to IEC 62778, risk group RG0
- Energy savings of up to 85 % (compared to traditional incandescent lamps)
- Instant 100 % light, no warm-up time
- No UV and near-IR radiation in the light beam
- Reliable operation thanks to brand quality

#### **Product features**

- Color rendering index  $R_a$ ;  $\ge 80$
- Not dimmable
- Mercury-free lamps



## TECHNICAL DATA

### Electrical data

Nominal wattage	12 W
Construction wattage	12.00 W
Nominal voltage	100240 V
Claimed equiv. conventional lamp power	100 W
Nominal current	73 mA
Type of current	AC
Operating frequency	50/60 Hz
Mains frequency	50/60 Hz
Power factor $\lambda$	> 0.70

### Photometrical data

Luminous flux	1521 lm
Nominal useful luminous flux 90°	1521 lm
Luminous efficacy	126 lm/W
Lumen main.fact.at end of nom.life time	0.70
Light color (designation)	Daylight
Color temperature	6500 K
Color rendering index Ra	≥80
Light color	865
Standard deviation of color matching	≤6 sdcm

# Light technical data

Beam angle	200 °
Starting time	< 0.5 s

# **Dimensions & Weight**

Overall length	120.00 mm
Diameter	60.00 mm
Maximum diameter	60 mm
Product weight	34.00 g

# Temperatures & operating conditions

Ambient temperature range	-20+40 °C

# Lifespan

Number of switching cycles	100000
Additional product data	
Base (standard designation)	E27
Mercury content	0.0 mg
Mercury-free	Yes
Capabilities	
Dimmable	No
Certificates & Standards	
Type of protection	IP20
Country-specific categorizations	
Order reference	LVCLAH 12W/8651
LOGISTICAL DATA	
Temperature range at storage	-20+80 °C
Energy labelling regulation data acc EU 2019/2015	
Light source cap-type (or other electric interface)	E27
	100.00

Light source cap-type (of other electric interface)	
Length	120.00 mm
Height	60.00 mm
Width	60.00 mm

# LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075656192	Folding box 1	61 mm x 61 mm x 125 mm	58.00 g	0.47 dm <sup>3</sup>
4099854021190	Shipping box 10	315 mm x 132 mm x 136 mm	600.00 g	5.65 dm <sup>3</sup>
4058075656208	Shipping box 10	315 mm x 132 mm x 139 mm	708.00 g	5.78 dm <sup>3</sup>

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

# DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.