

# PRODUCT DATASHEET LED VALUE CLAS A 10 W/2700 K E27 GEN4

LED VALUE CLASSIC A | LED lamps, classic bulb shape



#### Areas of application

- Domestic applications
- General illumination
- Outdoor applications only in suitable luminaires

#### **Product benefits**

- No "Blue Light" Hazard (according to IEC62778)
- Photobiological safety according to IEC 62778, risk group RG0
- Energy savings of up to 85 % (compared to traditional incandescent lamps)
- Instant 100 % light, no warm-up time
- No UV and near-IR radiation in the light beam
- Reliable operation thanks to brand quality

#### **Product features**

- Color rendering index  $R_a$ ;  $\ge 80$
- Not dimmable
- Mercury-free lamps



## TECHNICAL DATA

#### Electrical data

Nominal wattage	10 W
Construction wattage	10.00 W
Nominal voltage	220240 V
Claimed equiv. conventional lamp power	75 W
Nominal current	84 mA
Type of current	AC
Operating frequency	5060 Hz
Mains frequency	5060 Hz
Power factor $\lambda$	> 0.50

#### Photometrical data

Luminous flux	1055 lm
Nominal useful luminous flux 90°	1055 lm
Luminous efficacy	105 lm/W
Lumen main.fact.at end of nom.life time	0.70
Light color (designation)	Warm White
Color temperature	2700 K
Color rendering index Ra	≥80
Light color	827
Standard deviation of color matching	≤6 sdcm
Rated LLMF at 6,000 h	0.80

## Light technical data

Beam angle	180 °
Warm-up time (60 %)	< 0.50 s
Starting time	< 0.5 s

## **Dimensions & Weight**

Overall length	118.00 mm
Diameter	60.00 mm
Maximum diameter	60 mm
Product weight	32.00 g

# Temperatures & operating conditions

# Lifespan

Number of switching cycles	100000
Lumen maintenance at end of service lifetime	0.70
Rated lamp survival factor at 6,000 h	≥ 0.90

## Additional product data

Base (standard designation)	E27
Mercury content	0.0 mg
Mercury-free	Yes
Product remark	All technical parameters apply to the entire lamp / Due to the complex production process for light-emitting diodes, the typical values shown for the technical LED parameters are purely statistical values that do not necessarily match the actual technical parameters of each individual product, which can vary from the typical value

#### Capabilities

Dimmable No
-------------

# Certificates & Standards

Energy efficiency class	F <sup>1)</sup>
Energy consumption	10.00 kWh/1000h
Photobiological safety group acc. to EN62778	RG0

1) Energy efficiency class (EEC) on a scale of A++ (highest efficiency) to E (lowest efficiency)

# Country-specific categorizations

# Energy labelling regulation data acc EU 2019/2015

Light source cap-type (or other electric interface)	E27
Correlated colour temperature type	SINGLE_VALUE
Length	118.00 mm
Height	60.00 mm
Width	60.00 mm
EPREL ID	1403213
Model number	AC24697

## DOWNLOAD DATA

Photometric and lighting design files
IES file (IES)

Document name

LED VALUE CLA75 11W 2700K

## LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075202146	Folding box 1	61 mm x 61 mm x 118 mm	69.00 g	0.44 dm <sup>3</sup>
4058075351530	Shipping box 10	318 mm x 132 mm x 135 mm	572.00 g	5.67 dm <sup>3</sup>

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

#### DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.