

# PRODUCT DATASHEET LED VALUE CLAS B 4.7 W/6500 K E14

LED VALUE CLASSIC B | LED lamps, classic mini-candle shape



#### Areas of application

- General illumination
- Domestic applications
- Chandeliers
- Outdoor use in suitable outdoor luminaires only

#### **Product benefits**

- Lower energy consumption than incandescent or halogen lamps
- Simple direct replacement for conventional incandescent lamps
- Instant 100 % light, no warm-up time

### **Product features**

- LED alternative to conventional lamps
- Not dimmable
- Good color rendering CRI  $\geq$  80 and color stability throughout the life of the lamp



#### **TECHNICAL DATA**

#### Electrical data

Nominal wattage	4.7 W
Construction wattage	4.70 W
Nominal voltage	220240 V
Claimed equiv. conventional lamp power	40 W
Nominal current	43 mA
Type of current	AC
Operating frequency	50/60 Hz
Mains frequency	50/60 Hz
Power factor $\lambda$	> 0.50

#### Photometrical data

Luminous flux	470 lm
Luminous efficacy	100 lm/W
Light color (designation)	Cool Daylight
Color temperature	6500 K
Color rendering index Ra	80
Light color	865
Standard deviation of color matching	≤6 sdcm

#### Light technical data

Beam angle	220 °
Starting time	≤ 0.5 s

# **Dimensions & Weight**

Overall length	96.00 mm
Diameter	37.00 mm
Maximum diameter	37 mm
Product weight	15.00 g

# Temperatures & operating conditions

Ambient temperature range	-20+45 °C
Lifespan	

#### Litespan

Lifespan L70/B50 at 25 °C	15000 h

Number of switching cycles	100000		
Additional product data			
Base (standard designation)	E14		
Mercury content	0.0 mg		
Mercury-free	Yes		
Design / version	Frosted		
Capabilities			
Dimmable	No		
Certificates & Standards			
Type of protection	IP20		
Standards	CB / EMC / SAA / ROHS		
Photobiological safety group acc. to EN62778	RG0		
Country-specific categorizations			
Order reference	LVCLB40 4,7W/86		
LOGISTICAL DATA			
Temperature range at storage	-20+80 °C		
Energy labelling regulation data acc EU 2019/2015			
Lighting technology used	LED		
Light source cap-type (or other electric interface)	E14		

Height	37.00 mm
Width	37.00 mm

96.00 mm

#### Safety advice

Length

- Do not touch the lamp if broken.

- Must not be used if outer bulb is defective.

### LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4099854310348	Folding box 1	38 mm x 38 mm x 102 mm	22.00 g	0.15 dm <sup>3</sup>

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4099854310355	Shipping box 10	198 mm x 84 mm x 113 mm	279.00 g	1.88 dm <sup>3</sup>

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

#### DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.