

# PRODUCT DATASHEET HALOLINE 300 W 220...240 V R7S

HALOLINE® Standard | Double ended halogen lamps with tube base



#### Areas of application

- Ideal for emphasizing and accentuating buildings
- General illumination
- Entrance lighting
- Pathway lighting
- Garden lighting
- Traffic areas
- Shops
- Restaurants, hotels and similar prestigious applications
- Outdoor applications only in suitable luminaires

### **Product benefits**

- Brilliant accent light
- No transformer required
- Contains no mercury

#### Product features

- Average life: 2,000 h
- 100 % dimmable
- Color rendering index Ra: 100
- Color temperature: 3,000 K
- Burning position: p15

### **TECHNICAL DATA**

### Electrical data

Nominal wattage	300 W
Construction wattage	300.00 W
Nominal voltage	220240 V

## Photometrical data

Luminous flux	4400 lm
Luminous efficacy	14 lm/W
Light color (designation)	Warm White
Color temperature	2900 K
Color rendering index Ra	100
Light color	1029
UV protection	No

## Light technical data

Starting time 0 s	s
-------------------	---

## Dimensions & Weight

Overall length	119.60 mm
Diameter	12.00 mm
Product weight	7.00 g

## Additional product data

Base (standard designation)	R7s
Mercury-free	Yes
Design / version	Tube
Product remark	Fuse protection with indicated values recommended acc. to IEC60357, EN60357 / Banned from 1.9.2009 as per EU phase-out plan

## Capabilities

Dimmable	Yes
Burning position	Any

# Country-specific categorizations

ILCOS	HDG-300-220/240-R7s-114,2
Order reference	64705 300W 220-

# Energy labelling regulation data acc EU 2019/2015

Light source cap-type (or other electric interface)	R7s
---	-----

Length	119.60 mm
Height	12.00 mm
Width	12.00 mm

### Safety advice

- Do not touch the lamp if broken.
- Must not be used if outer bulb is defective.
- Lamp to be used only in a closed luminaire.
- Not designed as a replacement for conventional lighting in private household.

#### LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4050300824642	Blister 1	185 mm x 89 mm x 12 mm	12.00 g	0.20 dm <sup>3</sup>
4050300824659	Shipping box 20	247 mm x 94 mm x 199 mm	358.00 g	4.62 dm <sup>3</sup>

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

### **DISCLAIMER**

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.