

# PRODUCT DATASHEET DST STICK 20 W/865 E27

OSRAM DULUXSTAR® STICK | Compact fluorescent integrated, stick shape



## Areas of application

- General illumination
- Domestic applications
- Wherever compact and efficient lamps are needed
- Wherever cold light colors are needed
- Outdoor use in enclosed and ventilated luminaires only

## **Product benefits**

- Fast return on investment
- Up to 80 % less energy consumption compared with ordinary light bulbs

#### **Product features**

- Available in 2 light colors: 827 and 865
- Also available in activating light color LUMILUX® Cool Daylight
- Average life: up to 8,000 h



tháng 9 11, 2025, 11:35:46 DST STICK 20 W/865 E27


## **TECHNICAL DATA**

## Electrical data

| Nominal wattage      | 20 W     |
|----------------------|----------|
| Construction wattage | 20.00 W  |
| Nominal voltage      | 220240 V |
| Nominal current      | 200 mA   |
| Operating frequency  | 5060 Hz  |
| Mains frequency      | 5060 Hz  |

## Photometrical data

| Luminous flux             | 1180 lm  |
|---------------------------|----------|
| Light color (designation) | Daylight |
| Color temperature         | 6500 K   |
| Color rendering index Ra  | ≥80      |
| Light color               | 865      |



## Dimensions & Weight

| Overall length | 161.00 mm |
|----------------|-----------|
| Diameter       | 45,0 mm   |
| Product weight | 80.00 g   |

## Additional product data

| Base (standard designation) | E27    |
|-----------------------------|--------|
| Mercury content             | 1.8 mg |
| Mercury-free                | No     |

## Capabilities

|  | Dimmable | No |
|--|----------|----|
|--|----------|----|

## Country-specific categorizations

| ILCOS           | FBT-20/65/1B-220/240-E27 |
|-----------------|--------------------------|
| Order reference | DSTAR 20W/865 2          |

## Energy labelling regulation data acc EU 2019/2015

| Light source cap-type (or other electric interface) | E27       |
|-----------------------------------------------------|-----------|
| Length                                              | 161.00 mm |
| Height                                              | 45,0 mm   |
| Width                                               | 45,0 mm   |

### Safety advice

- In case of lamp breakage: www.ledvance.com/brokenlamp

- Not for use with external dimmers or electronic switches.

## DOWNLOAD DATA

|   | Photometric and lighting design files | Document name |
|---|---------------------------------------|---------------|
| 1 | Spectral power distribution           | 349641_FL_865 |

## LOGISTICAL DATA

| Product code  | Packaging unit (Pieces/Unit) | Dimensions (length x width x height) | Gross weight | Volume                |
|---------------|------------------------------|--------------------------------------|--------------|-----------------------|
| 4050300926414 | Folding box<br>1             | 52 mm x 52 mm x 164 mm               | 0.10 g       | 0.44 dm <sup>3</sup>  |
| 4008321873507 | Shipping box<br>20           | 268 mm x 216 mm x 179 mm             | 2.11 g       | 10.36 dm <sup>3</sup> |
| 4058075011137 | Shipping box<br>20           | 262 mm x 209 mm x 179 mm             | 2055.00 g    | 9.80 dm <sup>3</sup>  |

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

### DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.