PRODUCT DATASHEET
DULUX D 26 W/6500 K G24d-3

OSRAM DULUX® D | CFLni, 2 tubes, with 2-pin base for CCG operation

Areas of application

– Offices, public buildings
– Shops
– Supermarkets and department stores
– Hotels, restaurants
– Industry

Product benefits

– Improved maintenance

Product features

– Good color rendering index
– Short and compact pin-base lamp with double-turn tubes
– Single-ended two-pin plug-in G24d base

TECHNICAL DATA

Electrical data

Nominal wattage	26 W
Construction wattage	26.00 W

Photometrical data

Luminous flux	1700 lm
Luminous flux at 25 °C	1710 lm
Color temperature	6500 K
Color rendering index Ra	80…89
Light color	865
Rated LLMF at 2,000 h	0.77
Rated LLMF at 4,000 h	0.70
Rated LLMF at 6,000 h	0.69
Rated LLMF at 8,000 h	0.68
Rated lamp efficacy (standard co.)	65 lm/W

Dimensions & Weight

Overall length	170.00 mm
Diameter	13.00 mm
Maximum diameter	11 mm
Product weight	50.00 g

Temperatures & operating conditions

Rated ambient temp.w.max.luminous	25.0 °C

Lifespan

Rated lamp survival factor at 2,000 h	0.99
Rated lamp survival factor at 4,000 h	0.99
Rated lamp survival factor at 6,000 h	0.95
Rated lamp survival factor at 8,000 h	0.81
Operation mode LLMF/LSF	50 Hz

Additional product data

Base (standard designation)	G24d-3
Mercury content	1.3 mg

Capabilities

Suitable for indoor	Yes

Certificates & Standards

Energy efficiency class	B
Energy consumption	31.43 kWh/1000h

Country-specific categorizations

Order reference	DULUX D 26W/865

Energy labelling regulation data acc EU 2019/2015

Light source cap-type (or other electric interface)	G24d-3
Length	172.00 mm
Height	13.00 mm
Width	13.00 mm

EQUIPMENT / ACCESSORIES

– Suitable for operation on conventional control gear

Safety advice

– In case of lamp breakage: www.ledvance.com/brokenlamp

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4008321830999	Folding box 1	36 mm x 36 mm x 179 mm	60.00 g	0.23 dm³
4008321831002	Shipping box 10	187 mm x 81 mm x 196 mm	685.00 g	2.97 dm³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.