

PRODUCT DATASHEET DULUX D/E 26 W/3000 K G24q-3

OSRAM DULUX® D/E | CFLni, 2 tubes, with 4-pin base for ECG operation



Areas of application

- Offices, public buildings
- Shops
- Supermarkets and department stores
- Hotels, restaurants
- Industry

Product benefits

- Extremly economical
- Good quality of light

Product features

- Short and compact pin-base lamp with double-turn tubes
- Single-ended four-pin plug-in G24q base



TECHNICAL DATA

Electrical data

Nominal wattage	26 W
Construction wattage	26.00 W

Photometrical data

Luminous flux	1800 lm
Color temperature	3000 K
Color rendering index Ra	8089
Light color	830
Rated LLMF at 2,000 h	0.89
Rated LLMF at 4,000 h	0.86
Rated LLMF at 6,000 h	0.84
Rated LLMF at 8,000 h	0.82
Rated LLMF at 12,000 h	0.79
Rated LLMF at 16,000 h	0.78
Rated LLMF at 20,000 h	0.76
Rated lamp efficacy (standard co.)	69 lm/W

Dimensions & Weight

Overall length	165.00 mm
Diameter	12.00 mm
Product weight	49.00 g

Temperatures & operating conditions

	25.0 °C
--	---------

Lifespan

Rated lamp survival factor at 2,000 h	0.99
Rated lamp survival factor at 4,000 h	0.99
Rated lamp survival factor at 6,000 h	0.99
Rated lamp survival factor at 8,000 h	0.99
Rated lamp survival factor at 12,000 h	0.95
Rated lamp survival factor at 16,000	0.81
Rated lamp survival factor at 20,000 h	0.50
Operation mode LLMF/LSF	HF

Additional product data

Base (standard designation)	G24q-3
Mercury content	1.4 mg

Capabilities

Country-specific categorizations

Order reference	DULUX D/E 26W/8

Energy labelling regulation data acc EU 2019/2015

Light source cap-type (or other electric interface)	G24q-3
Length	165.00 mm
Height	12.00 mm
Width	12.00 mm

EQUIPMENT / ACCESSORIES

- Suitable for operation on electronic control gear

Safety advice

- In case of lamp breakage: www.ledvance.com/brokenlamp

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4008321830494	Folding box 1	36 mm x 36 mm x 179 mm	59.00 g	0.23 dm ³
4008321830500	Shipping box 10	187 mm x 81 mm x 196 mm	665.00 g	2.97 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.