

PRODUCT DATASHEET

DULUX S 11 W/830

OSRAM DULUX® S | Short CFLni, with 2-pin base for CCG operation



Areas of application

- Ideal for cost-effective creative illumination and decoration
- Offices, public buildings
- Shops
- Supermarkets and department stores
- Hotels, restaurants

Product benefits

- Improved maintenance

Product features

- Good color rendering index
- Short and compact pin-base lamps with single-turn tubes
- Single-ended two-pin plug-in G23 base




TECHNICAL DATA

Electrical data

| | |
|----------------------|---------|
| Nominal wattage | 11 W |
| Construction wattage | 12.40 W |
| Nominal voltage | 91 V |
| Nominal current | 0.16 A |


Photometrical data


| | |
|---------------------------|--------------------|
| Luminous flux | 900 lm |
| Luminous efficacy | 73 lm/W |
| Light color (designation) | LUMILUX Warm White |
| Color temperature | 3000 K |
| Color rendering index Ra | ≥80 |
| Light color | 830 |
| Rated LLMF at 2,000 h | 0.85 |
| Rated LLMF at 4,000 h | 0.78 |
| Rated LLMF at 6,000 h | 0.76 |
| Rated LLMF at 8,000 h | 0.75 |



349617_FL_830

Dimensions & Weight





| | |
|---------------------------------------------|-----------|
| Overall length | 236.50 mm |
| Length with base excl. base pins/connection | 214,00 mm |
| Diameter | 12.00 mm |
| Tube diameter | 12 mm |
| Product weight | 30.7 g |

Temperatures & operating conditions

| | |
|---------------------------|-------------|
| Ambient temperature range | -5...+40 °C |
|---------------------------|-------------|

Lifespan

| | |
|---------------------------------------|---------|
| Service life | 6500 h |
| Rated lamp survival factor at 2,000 h | 0.99 |
| Rated lamp survival factor at 4,000 h | 0.99 |
| Rated lamp survival factor at 6,000 h | 0.99 |
| Rated lamp survival factor at 8,000 h | 0.81 |
| Lifespan B50 | 10000 h |

Additional product data

| | |
|-----------------------------|--------|
| Base (standard designation) | G23 |
| Mercury content | 1.6 mg |

Capabilities

| | |
|----------|----|
| Dimmable | No |
|----------|----|

Certificates & Standards

| | |
|-------------------------|-----------------|
| Energy efficiency class | G |
| Energy consumption | 13.00 kWh/1000h |

Country-specific categorizations

| | |
|-------|------------------|
| ILCOS | FSD-11/830-I-G23 |
|-------|------------------|

| | |
|-----------------|-----------------|
| Order reference | DULUX S 11W/830 |
|-----------------|-----------------|

Energy labelling regulation data acc EU 2019/2015

| | |
|-----------------------------------------------------|--------------|
| Lighting technology used | CFLNI |
| Non-directional or directional | NDLS |
| Mains or non-mains | NMLS |
| Light source cap-type (or other electric interface) | G23 |
| Connected light source (CLS) | No |
| Color-tuneable light source | No |
| Envelope | No |
| High luminance light source | No |
| Anti-glare shield | No |
| Correlated colour temperature type | SINGLE_VALUE |
| Claim of equivalent power | No |
| Length | 236.50 mm |
| Height | 12.00 mm |
| Width | 12.00 mm |
| Chromaticity coordinate x | 0,440 |
| Chromaticity coordinate y | 0,403 |
| Beam angle correspondence | SPHERE_360 |
| EPREL ID | 546493 |
| Model number | AC34268 |

EQUIPMENT / ACCESSORIES




- Suitable for operation on conventional control gear

Safety advice

- In case of lamp breakage: www.ledvance.com/brokenlamp

DOWNLOAD DATA

| Documents and certificates | Document name |
|---------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------|
|  Declarations of conformity | EC Declaration of Conformity - 2021 9C1-4077883-EN-00 - DULUX S |

| Documents and certificates | | Document name |
|-----------------------------------------------------------------------------------|-----------------------------|---------------------------------------------------------------------------------|
|  | Certificates | EAC RU C-DE.HA46.B.01131_21 21.05.2021-20.05.2026 Expert Certification - CFLpin |
|  | Certificates | EAC N RU D-DE.MU62.B.00933_20 06.03.2020-05.03.2025 Prommash Test - CFLpin |
| Photometric and lighting design files | | Document name |
|  | Spectral power distribution | 349617_FL_830 |

LOGISTICAL DATA

| Product code | Packaging unit (Pieces/Unit) | Dimensions (length x width x height) | Gross weight | Volume |
|---------------|------------------------------|--------------------------------------|--------------|----------------------|
| 4050300025759 | Folding box 1 | 23 mm x 36 mm x 242 mm | 49.38 g | 0.20 dm ³ |
| 4050300258010 | Shipping box 10 | 190 mm x 54 mm x 257 mm | 546.77 g | 2.64 dm ³ |

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.