

PRODUCT DATASHEET

HE 35 W/840

LUMILUX® T5 HE® | Tubular fluorescent lamps 16 mm, high efficiency, with G5 base



Areas of application

- Public buildings
- Offices
- Shops
- Supermarkets and department stores
- Industry
- Outdoor applications only in suitable luminaires

Product benefits

- Up to 20 % more economical than LUMILUX® T8

Product features

- Very good lumen maintenance: 90 % throughout the service lifetime of the lamp
- Good color rendering index
- Dimmable



TECHNICAL DATA

Electrical data

Nominal wattage	35 W
Construction wattage	35.50 W
Nominal voltage	220 V
Rated lamp efficacy (HF data 25 °C)	94

Photometrical data

Luminous flux	3320 lm
Luminous efficacy	94 lm/W
Luminous flux at 25 °C	3320 lm
Luminous flux at 35 °C	3650 lm
Light color (designation)	LUMILUX Cool White
Color temperature	4000 K
Color rendering index Ra	≥80
Light color	840
Rated LLMF at 2,000 h	0.95
Rated LLMF at 4,000 h	0.93
Rated LLMF at 6,000 h	0.92
Rated LLMF at 8,000 h	0.90
Rated LLMF at 12,000 h	0.90
Rated LLMF at 16,000 h	0.90
Rated LLMF at 20,000 h	0.89
Rated lamp efficacy (HF data 25 °C)	94

Dimensions & Weight

Overall length	1449.00 mm
Length with base excl. base pins/connection	1449 mm
Diameter	16.00 mm
Tube diameter	16 mm
Maximum diameter	16 mm
Product weight	115.00 g

Temperatures & operating conditions

Rated ambient temp.w.max.luminous	35.0 °C
-----------------------------------	---------

Lifespan

Rated lamp survival factor at 2,000 h	0.99
Rated lamp survival factor at 4,000 h	0.99
Rated lamp survival factor at 6,000 h	0.99
Rated lamp survival factor at 8,000 h	0.99
Rated lamp survival factor at 12,000 h	0.99
Rated lamp survival factor at 16,000	0.97
Rated lamp survival factor at 20,000 h	0.85
Operation mode LLMF/LSF	HF

Additional product data

Base (standard designation)	G5
Mercury content	1.2 mg
Product remark	Suitable for ECG operation only / Lamp designed for internal luminaire temperatures of 30...40 °C; optimum luminous flux achieved at 35 °C

Capabilities

Suitable for indoor	Yes
---------------------	-----

Certificates & Standards

Energy efficiency class	A+
Energy consumption	39.05 kWh/1000h

Country-specific categorizations

ILCOS	FDH-35/40/1B-L/P-G5-16/1449
Order reference	HE 35W/840

Energy labelling regulation data acc EU 2019/2015

Light source cap-type (or other electric interface)	G5
Length	1449.00 mm
Height	16.00 mm
Width	16.00 mm

Safety advice

– In case of lamp breakage: www.ledvance.com/brokenlamp

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4008321672391	Sleeve 1	1,464 mm x 18 mm x 18 mm	138.00 g	0.47 dm³
4008321672407	Shipping box 20	1,511 mm x 104 mm x 88 mm	3498.00 g	13.83 dm³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.