

PRODUCT DATASHEET

L 30 W/

LUMILUX® T8 | Tubular fluorescent lamps 26 mm, with G13 bases



Areas of application

- Public buildings
- Office lighting
- Industry
- Shops
- Supermarkets and department stores
- Street lighting
- Outdoor applications only in suitable luminaires

Product benefits

- Proven lamp technology

Product features

- Very good lumen maintenance: 90 % throughout the service lifetime of the lamp
- Good color rendering index
- Dimmable



TECHNICAL DATA

Electrical data

Nominal wattage	30 W
Construction wattage	30.00 W
Nominal voltage	220 V
Rated lamp efficacy (HF data 25 °C)	Under clarification by authority and standardization body

Photometrical data

Luminous flux at 25 °C	2400 lm
Color rendering index Ra	80
Light color	8
Rated lamp efficacy (HF data 25 °C)	Under clarification by authority and standardization body

Dimensions & Weight

Overall length	894.60 mm
Length with base excl. base pins/connection	895,00 mm
Diameter	26.00 mm
Tube diameter	26 mm
Product weight	130.00 g

Lifespan

Service life	16000 h ¹⁾
--------------	-----------------------

¹⁾ With preheat ECG

Additional product data

Base (standard designation)	G13
Mercury content	3.0 mg

Capabilities

Dimmable	Yes
----------	-----

Country-specific categorizations

Order reference	L 30W/840LUMILU
-----------------	-----------------

Energy labelling regulation data acc EU 2019/2015

Light source cap-type (or other electric interface)	G13
---	-----

Length	895.00 mm
Height	26.00 mm
Width	26.00 mm

Safety advice

– In case of lamp breakage: www.ledvance.com/brokenlamp

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4050300926896	Sleeve 1	910 mm x 29 mm x 29 mm	150.00 g	0.77 dm ³
4050300927084	Shipping box 25	955 mm x 151 mm x 153 mm	4039.00 g	22.06 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.