

# PRODUCT DATASHEET

## L 36 W/640

Basic T8 | Tubular fluorescent lamps 26 mm, with G13 bases



## TECHNICAL DATA

### Electrical data

Nominal wattage	36 W
Construction wattage	36.00 W
Nominal voltage	220 V
Rated lamp efficacy (HF data 25 °C)	Under clarification by authority and standardization body

### Photometrical data

Luminous flux	2850 lm
Luminous efficacy	79 lm/W
Luminous flux at 25 °C	2850 lm
Color temperature	4000 K
Color rendering index Ra	≥60
Light color	640
Rated lamp efficacy (HF data 25 °C)	Under clarification by authority and standardization body

### Dimensions & Weight

Overall length	1200.00 mm
Length with base excl. base pins/connection	1200 mm
Diameter	26.00 mm
Tube diameter	26 mm
Product weight	147.00 g

### Lifespan

Service life	5000 h
--------------	--------

### Additional product data

Base (standard designation)	G13
Mercury content	9.0 mg

### Country-specific categorizations

ILCOS	FD-36/640-E-G13-26/1200
Order reference	L 36W/640

### Energy labelling regulation data acc EU 2019/2015

Light source cap-type (or other electric interface)	G13
Length	1200.00 mm

Height	26.00 mm
Width	26.00 mm

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4008321966261	Sleeve 1	1,215 mm x 29 mm x 29 mm	198.00 g	1.02 dm <sup>3</sup>
4008321966278	Shipping box 25	1,234 mm x 150 mm x 155 mm	4510.00 g	28.69 dm <sup>3</sup>

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.