

# PRODUCT DATASHEET L 32 W/865 G10Q

LUMILUX® T9 C | Circular fluorescent lamps 29 mm, with G10Q base



## Areas of application

- Public buildings
- Restaurants
- Industry
- Shops
- Supermarkets and department stores
- Hotels

## **Product benefits**

- Excellent uniform illumination with no shadows

## Product features

- Good color rendering index
- Single-ended round fluorescent lamp
- Dimmable




## TECHNICAL DATA

## Electrical data

Nominal wattage	32 W	
Construction wattage	32.00 W	
Nominal voltage	84 V	
Rated lamp efficacy (HF data 25 °C)	Under clarification by authority and standardization body	

## Photometrical data

Luminous flux	2200 lm	
Luminous efficacy 68 lm/W		
Luminous flux at 25 °C	2150 lm	
Light color (designation)	LUMILUX Cool Daylight	
Color temperature	6500 K	
Color rendering index Ra	8089	
Light color	865	
Rated lamp efficacy (HF data 25 °C)	Under clarification by authority and standardization body	



349641\_FL\_865

## Dimensions & Weight

Overall length	304.80 mm
Diameter	305 mm
Tube diameter	29 mm
Product weight	192.00 g

## Lifespan

	00001
Service life	6300 h

## Additional product data

Base (standard designation)	G10q	
Mercury content	3.0 mg	
Design / version	LUMILUX version	

## Country-specific categorizations

ILCOS	FSC-32/865-E-G10q-29/305
Order reference	L 32W/865 C G10

## Energy labelling regulation data acc EU 2019/2015

Light source cap-type (or other electric interface)	G10q
Length	305.00 mm
Height	305 mm
Width	305 mm

#### **EQUIPMENT / ACCESSORIES**

- Suitable for operation on electronic and conventional control gears

## Safety advice

- In case of lamp breakage: www.ledvance.com/brokenlamp

#### **DOWNLOAD DATA**

Photometric and lighting design files	Document name
Spectral power distribution	349641_FL_865

## LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4008321530783	Sleeve 1	309 mm x 306 mm x 38 mm	322.00 g	3.59 dm <sup>3</sup>
4008321530790	Shipping box 12	452 mm x 323 mm x 320 mm	4305.00 g	46.72 dm <sup>3</sup>

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

## **DISCLAIMER**

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.