

PRODUCT DATASHEET

L 40 W/840 C G10Q

LUMILUX® T9 C | Circular fluorescent lamps 29 mm, with G10Q base



Areas of application

- Public buildings
- Restaurants
- Industry
- Shops
- Supermarkets and department stores
- Hotels

Product benefits

- Excellent uniform illumination with no shadows

Product features

- Good color rendering index
- Single-ended round fluorescent lamp
- Dimmable



TECHNICAL DATA**Electrical data**

Nominal wattage	40 W
Construction wattage	40.00 W
Nominal voltage	115 V
Rated lamp efficacy (HF data 25 °C)	Under clarification by authority and standardization body

Photometrical data

Luminous flux	3000 lm
Luminous efficacy	75 lm/W
Color temperature	4000 K
Color rendering index Ra	80...89
Light color	840
Rated lamp efficacy (HF data 25 °C)	Under clarification by authority and standardization body

Dimensions & Weight

Overall length	406.00 mm
Diameter	29.00 mm
Product weight	261.00 g

Lifespan

Service life	5000 h
--------------	--------

Additional product data

Base (standard designation)	G10q
Mercury content	3.6 mg
Design / version	LUMILUX version

Country-specific categorizations

Order reference	L 40W/840 C G10
-----------------	-----------------

Energy labelling regulation data acc EU 2019/2015

Light source cap-type (or other electric interface)	G10q
Length	406.00 mm
Height	29.00 mm
Width	29.00 mm

EQUIPMENT / ACCESSORIES

- Suitable for operation on electronic and conventional control gears
-

Safety advice

- In case of lamp breakage: www.ledvance.com/brokenlamp
-

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4008321646149	Sleeve 1	421 mm x 411 mm x 38 mm	451.00 g	6.58 dm ³
4008321646156	Shipping box 12	452 mm x 436 mm x 431 mm	5865.00 g	84.94 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.