

# PRODUCT DATASHEET LVED PRO 10/220...240/250 CS

LEDVANCE LED DRIVER PRO CS | Constant Current - Indoor - on/off



#### Areas of application

- Suitable for indoor SELV installations
- Suitable for LED luminaires and LED modules
- Suitable for build-in luminaries with adjustable current setting
- Suitable for luminaires of protection class II
- Hotels, shops, hospitality, residential interiors
- Offices
- Suitable for indoor applications.

### Product benefits

- High flexibility due to adjustable output currents via dip switch
- Small housing for flexible luminaire designs
- High quality of light thanks to low output ripple current

#### **Product features**

- Lifetime: up to 50,000 h (at max. tc temperature)
- Low ripple current < 4 %
- Power factor: 0.95
- Protection class II
- High reliability thanks to long lifetime
- Safety according to IEC/EN 61347-1, IEC/EN 61347-2-13, GB 19510.1, GB 19510.14
- EMC immunity according to CISPR15/EN 55015, IEC/ EN 61547, IEC/EN61000-3-2, GB/T17743, GB 17625.1
- Performance according to IEC 62384
- With CCC, CE, CB certificate
- RoHS compliant

# TECHNICAL DATA

# Electrical data

Nominal wattage	12.00 W	
Nominal output power 10 W		
Nominal voltage 220240 V		
Nominal output voltage 2542 V		
Input voltage AC 198264 V		
Nominal current 70 mA		
Nominal output current	90 mA / 120 mA / 150 mA / 180 mA / 220 mA / 250 mA <sup>1)</sup>	
Inrush current	< 10 A	
Mains frequency	5060 Hz	
Total harmonic distortion	20 %	
Power factor $\lambda$	0.95	
ECG efficiency	85 % <sup>2)</sup>	
Galvanic isolation	SELV	
Operating frequency	50/60 Hz	

<sup>1)</sup> Output current selectable by DIP SWITCH

# Dimensions & Weight

Length	87.00 mm
Width	35.00 mm
Height	24.00 mm
Product weight	72.00 g

# Colors & materials

Product color	White
Casing material	Plastic
Body material	Plastic

# Temperatures & operating conditions

Ambient temperature range	-20+50 °C
Maximum temperature at tc test point	80 °C
Max.housing temperature in case of fault	110 °C
Temperature range in operation	-20+50 °C

# Capabilities

Dimmable	No
Dimming interface	Not dimmable

<sup>2)</sup> At full load

Overheating protection	No
Overload protection	Yes
No-load proof	Yes
Short-circuit protection	Yes

#### Certificates & Standards

Approval marks – approval	CB / CCC / CE / RoHS
Protection class	П
Type of protection	IP20

#### LOGISTICAL DATA

Temperature range at storage	-40+80 °C
------------------------------	-----------

# LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075502482	Unpacked 1	36 mm x 26 mm x 89 mm	84.00 g	0.08 dm <sup>3</sup>
4058075502499	Shipping box 40	199 mm x 195 mm x 133 mm	3391.00 g	5.16 dm <sup>3</sup>

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

#### **DISCLAIMER**

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.