

PRODUCT DATASHEET LVED PRO LVED PRO 150/22

LED Pro Outdoor CC Driver | Constant current ECG for LED modules



Areas of application

- Outdoor applications
- Street and urban lighting
- Sports halls

Product benefits

- Safety requirement due to overload, overtemperature, short-circuit protection
- Long lifetime
- High surge protection: up to 6 kV

Product features

- Lifetime up to 50,000 h

TECHNICAL DATA

Electrical data

Nominal wattage	150.00 W
Nominal voltage	220240 V
Mains frequency	5060 Hz
Power factor λ	0.95

Dimensions & Weight

Length	217.00 mm
Width	54.00 mm
Height	32.00 mm
Product weight	600.00 g

Temperatures & operating conditions

Ambient temperature range	-40+50 °C
Maximum temperature at tc test point	85 °C
Max.housing temperature in case of fault	110 °C
Temperature range in operation	-40+50 °C

Capabilities

Dimmable	No
=	

Certificates & Standards

Protection class	1
------------------	---

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075353183	Folding box 1	242 mm x 82 mm x 49 mm	641.00 g	0.97 dm ³
4058075353190	Shipping box 20	434 mm x 262 mm x 226 mm	13334.00 g	25.70 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.